# Lumirror. FA3

## **Applications**

- Specialized thermal transfer ribbon
- Coversheet

— Mono Layer PET

## MONO LAYER PET FILM

### Summary

FA3 is a specialized film for thermal transfer ribbon, which has good thermal stability, smoother surface and good handling properties.

umirror FA



#### ✓ Technical Data \*\*

PROPERTIES		METHOD	UNITS	TYPICAL VALUES
Thickness		-	micron	5.1
Nominal Yield		-	m2/kg	140.1
F-5	MD	ASTM D882	Мра	114
	TD			98
Tensile Strength at Break	MD	ASTM D882	Мра	288
	TD			242
Elongation at Break	MD	ASTM D882	%	100
	TD			110
Heat Shrinkage (150°C for 30 minutes)	MD	ASTM D1204	% —	2
	TD			0.7
Coefficient of Friction	A-side vs. B-side	ASTM D1894	$\mu_{S}$	0.6
			$\mu_{D}$	0.5
Haze (1 sheet)		ASTM 1003	%	3.7


#### Key Features

- Good mechanical properties with excellent heat stability
- · Smoother surface with good handling properties

#### Similar Products

- F53
- F531

#### Winding Direction



#### \* These values do not constitute specific binding specifications

DISCLAIMER: This information is believed to be correct as of the date of issue. Toray Plastics (America), Inc. MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE AND TAKES NO RESPONSIBILITY REGARDING THE SUITABILITY OF THIS INFORMATION FOR THE USER'S INTENDED PURPOSES OR FOR THE CONSEQUENCE OF ITS USE. User is responsible for determining whether the Toray Plastics (America), Inc. product is fit for a particular purpose and suitable for user's method or use of application. Given the variety of factors that can affect the use and application of Toray Plastics (America), Inc. products, which are uniquely within the user's knowledge and control, it is essential that the user make its own tests to determine the safety and suitability of each Toray Plastics (America), Inc. product or product combination for its own purpose.