
LUMIRROR® U80

Applications

- Economy solar control window film
- Overlaminate
- Dyeing



VERY CLEAR THREE LAYER PET FILM

Summary

U80 is a very clear film with surface and optical properties that are strictly controlled by co-extrusion technology.

Lumirror U8



✓ Technical Data **

PROPERT	IES	METHOD	UNITS		TYPICAL VALUES	
Thickness		-	micron	12.2	17.8	23.4
Nominal Yield		-	m2/kg	58.5	40.1	30.5
F-5	MD	- ASTM D882	Mpa -	109	108	102
	TD			100	101	95
Tensile Strength at Break	MD	· ASTM D882	Mpa -	272	250	205
	TD			253	245	226
Elongation at Break	MD	· ASTM D882	% -	120	130	170
	TD			130	130	150
Heat Shrinkage (150°C for 30 minutes)	MD	· ASTM D1204	%	1.6	1.5	1.2
	TD			0.8	0.9	0.4
Heat Shrinkage (190°C for 5 minutes)	MD	• ASTM D1204	% •	3.1	2.9	2.1
	TD			1.5	1.3	0.7
Coefficient of Friction	A-side vs. B-side	ASTM D1894	μ_{s}	0.4	0.4	0.4
			μ_{D}	0.3	0.3	0.3
Haze (1 sheet)		ASTM 1003	%	2.0	2.0	2.0

Key Features

· Co-extruded three layer structure provides low friction and good handling properties

Similar Products

- U65
- TA30
- F7S

Winding Direction



* These values do not constitute specific binding specifications

DISCLAIMER: This information is believed to be correct as of the date of issue. Toray Plastics (America), Inc. MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE AND TAKES NO RESPONSIBILITY REGARDING THE SUITABILITY OF THIS INFORMATION FOR THE USER'S INTENDED PURPOSES OR FOR THE CONSEQUENCE OF ITS USE. User is responsible for determining whether the Toray Plastics (America), Inc. product is fit for a particular purpose and suitable for user's method or use of application. Given the variety of factors that can affect the use and application of Toray Plastics (America), Inc. products, which are uniquely within the user's knowledge and control, it is essential that the user make its own tests to determine the safety and suitability of each Toray Plastics (America), Inc. product or product combination for its own purpose.

Lumirror® is a registered trademark of Toray Industries, Inc. for its range of Polyester Films based on Polyethylene Terephthlate (PET).