


TORAYFAN[®] LGHX5

Applications

- Confections
- Snacks
- Bakery
- Pet food
- Ag/Chem
- Medical



Torayfan LGHX5

Product Data Sheet

HIGH BARRIER BOPP WITH INTEGRATED HERMETIC SEALANT LAYER

Summary

High barrier BOPP film with high hermeticity sealant applied opposite noncrazing vacuum deposited aluminum. Designed as a robust sealable barrier inner web for VFFS applications requiring excellent seal reliability and strength. The thick sealant layer provides secure seals in laminations to thick and stiff outer webs.



www.toraytpa.com rimarketing@toraytpa.com Toray Plastics (America), Inc. 50 Belver Avenue North Kingstown, RI 02852 1.800.453.6866

Torayfan LGHX5

Product Data Sheet

🖉 Technical Data 🗶

PROPERTIES		METHOD	UNITS	TYPICAL VALUES
- Thickness		-	micron	41
Nominal Yield		-	m²/kg	27
Tensile Strength at Break	MD	- ASTM D882	MPa	100
	TD			100
Young's Modulus	MD	- ASTM D882	MPa	900
	TD			900
Elongation at Break	MD	- ASTM D882	%	180
	TD			60
Coefficient of Friction (Sealant Side)		ASTM D1894 -	μ	0.11
			μ_{d}	0.10
Heat Seal Strength @ 121°C		1	g/25mm	3,800
Seal Initiation Temp (>200g/25mm)		1	°C	88
MVTR - 38°C, 90% RH		ASTM F1249	g/m²/day	0.16
O ₂ Barrier - 23°C, 0% RH		ASTM D3985	cc/m²/day	0.78

1 Sentinel Sealer model 12 ASL, 0.5 sec, 20 psi. UPPER: flat, Teflon™ coated. LOWER: rubber with glass cloth, unheated

- Key Features
- Superior hermetic sealant package
- Superior oxygen barrier
- Excellent moisture barrier
- Secure seals in laminations to thick and stiff outer webs
- Increased oil resistance


Similar Products

- MH5C
- MOTM

- Non craze metal surface
- Excellent hot tack and wide heat seal range

- Typical Structures
 - F62W/ink/ADH or PE/LGHX5
 - PA10/Ink/PE or ADH/LGHX5
- O.L./ink/Paper/PE or ADH/LGHX5

Winding Direction



* These values do not constitute specific binding specifications

DISCLAIMER: This information is believed to be correct as of the date of issue. Toray Plastics (America), Inc. MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE AND TAKES NO RESPONSIBILITY REGARDING THE SUITABILITY OF THIS INFORMATION FOR THE USER'S INTENDED PURPOSES OR FOR THE CONSEQUENCE OF ITS USE. User is responsible for determining whether the Toray Plastics (America), Inc. product is fit for a particular purpose and suitable for user's method or use of application. Given the variety of factors that can affect the use and application of Toray Plastics (America), Inc. products, which are uniquely within the user's knowledge and control, it is essential that the user make its own tests to determine the safety and suitability of each Toray Plastics (America), Inc. product or product combination for its own purpose.

Torayfan® is a registered trademark of Toray Industries, Inc. for its range of bi-oriented Polypropylene Films (BOPP)