

TORAYFAN MWX6

Applications

- Confections
- Snacks
- Bakery
- Pet Food
- Ag/Chem
- Medical

Aluminum Layer
Ultra Barrier Layer
Adhesion Layer
White Core Layer

Hermetic Sealant Layer

ONE SIDE HEAT SEALABLE METALLIZED WHITE CAVITATED BOPP FILM

Summary

White cavitated BOPP film with one side vacuum deposited Aluminum on Toray's Ultra Barrier Layer, one side heat sealable. Designed as an inside moisture and oxygen barrier metallized film for gas flushed applications.

Toray Plastics (America), Inc. 50 Belver Avenue North Kingstown, RI 02852 1.800.453.6866



Product Data Sheet

Torayfan MWX6

Technical Data *

PROPERTIES		METHOD	UNITS	TYPICAL VALUES
Thickness			μm	27.5
Nominal Yield			m²/kg	49.8
Tensile Strength at Break	MD	ASTM D882	Мра ——	100
	TD			200
Young's Modulus	MD	ASTM D882	Мра	1,600
	TD			2,900
Elongation at Break	MD	ASTM D882	%	160
	TD			40
Heat Shrinkage (140°C for 15 minutes)	MD	ASTM D1204	%	6.3
	TD			3.7
COE (Coolent Cide)		ASTM D1894	μ _s	0.9
COF (Sealant Side)			μ _D	0.75
Heat Seal Strength @ 121°C		1	g/25mm	430
SIT (>200g/25mm)		1	°C	85
MVTR - 38 °C, 90% RH		ASTM F1249	g/m²/day	0.078
O2TR - 23 °C, 0% RH		ASTM D3985	cc/m²/day	0.78

1 Sentinel Sealer model 12 ASL, 0.5 sec, 20 psi. UPPER: flat, teflon coated. LOWER: rubber with glass cloth, unheated

Key Features

- Superior Oxygen Barrier Gas Flushable
- Superior Moisture barrier
- Good yield (source reduction)
- Non craze metal surface
- Excellent hot tack and wide heat seal range

Similar Products

- MWS3
- PWX5

Typical Structures

- F61W/ink/PE or ADH/MWX6
- F62W/ink/PE or ADH/MWX6
- PA10/ink/PE or ADH/MWX6
- O.L./ink/MWX6

Winding Direction



* These values do not constitute specific binding specifications

DISCLAIMER: This information is believed to be correct as of the date of issue. Toray Plastics (America), Inc. MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE AND TAKES NO RESPONSIBILITY REGARDING THE SUITABILITY OF THIS INFORMATION FOR THE USER'S INTENDED PURPOSES OR FOR THE CONSEQUENCE OF ITS USE. User is responsible for determining whether the Toray Plastics (America), Inc. product is fit for a particular purpose and suitable for user's method or use of application. Given the variety of factors that can affect the use and application of Toray Plastics (America), Inc. products, which are uniquely within the user's knowledge and control, it is essential that the user make its own tests to determine the safety and suitability of each Toray Plastics (America), Inc. product or product combination for its own purpose.

O.L./ink/Paper/PE/MWX6