


TORAYFAN TX-CBS

Applications

- Confections
- Snacks
- Bakery
- Pet food
- Ag/Chem
- Medical



ONE SIDE TREATED, ONE SIDE HEAT SEALABLE TRANSPARENT BOPP FILM

Summary

One side treated with flame or corona treatment and one side heat sealable Bi-Axially Oriented Polypropylene film with excellent moisture barrier. Designed as the inside sealant web for clear moisture barrier applications. Can also be used as an unsupported web that can be surface printed.

Toray Plastics (America), Inc. 50 Belver Avenue North Kingstown, RI 02852 1.800.453.6866



Torayfan TX-CBS

🖉 Technical Data 🗡

Torayfan TX-CBS

PROPERTIES		METHOD	UNITS	TYPICAL VALUES
Thickness Range	·	-	micron	23-50
Thickness		-	micron	33
Nominal Yield		-	m²/kg	22
Tensile Strength at Break –	MD	– ASTM D882	Мра	100
	TD			300
Elongation at Break —	MD	- ASTM D882	%	200
	TD			50
Heat Shrinkage (100°C for 10 minutes) —	MD	- ASTM D2732-96	%	3
	TD			1
Coefficient of Friction –	A side	– ASTM D1894	μ _D	0.66
	B side		μ_{D}	0.45
Haze (1 sheet)		ASTM 1003	%	3.8
Wetting Tension –	Flame	– ASTM D2578	dyne/cm	48
	Corona			38
Heat Seal Strength @ 121°C		1	g/25mm	430
Seal Initiation Temp (>200g/25mm)		1	°C	91
MVTR - 38 °C, 90% RH		ASTM F1249	g/m²/day	1.86

1 Sentinel Sealer model 12 ASL, 0.5 sec, 20 psi. UPPER: flat, Teflon coated. LOWER: rubber with glass cloth, unheated

The product described is covered by one or more of the following patents or patents pending: US 6844078, EP 1474289.

Key Features

- Wide heat seal range in lap/fin/crimp seals
- Improved oil resistance
- Increased puncture resistance
- Increased stiffness
- Similar Products
- CBC
- CBH
- CBLS

- Typical Structures
- F61W/ink/PE or ADH/TX-CBS
- CBC/ink/PE or ADH/TX-CBS for enhanced MVTR
- PET/PE or ADH/TX-CBS
- Ink/TX-CBS

Winding Direction



* These values do not constitute specific binding specifications

DISCLAIMER: This information is believed to be correct as of the date of issue. Toray Plastics (America), Inc. MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE AND TAKES NO RESPONSIBILITY REGARDING THE SUITABILITY OF THIS INFORMATION FOR THE USER'S INTENDED PURPOSES OR FOR THE CONSEQUENCE OF ITS USE. User is responsible for determining whether the Toray Plastics (America), Inc. product is fit for a particular purpose and suitable for user's method or use of application. Given the variety of factors that can affect the use and application of Toray Plastics (America), Inc. products, which are uniquely within the user's knowledge and control, it is essential that the user make its own tests to determine the safety and suitability of each Toray Plastics (America), Inc. product or product combination for its own purpose.

Product Data Shee