

Lumirror. FA6

Applications

- · High gloss image transfer
- IMD

Surface Property Layer (Handling Enhanced)

Core Layer (Smooth Surface)

Lumirror FA6

Product Data Sheet

TWO LAYER PET FILM, ONE SIDE ROUGH, ONE SIDE SMOOTH

Summary

FA6 is a one side super smooth multilayer PET film type intended for high end liner release application with excellent handling.

www.toraytpa.com rimarketing@toraytpa.com Toray Plastics (America), Inc. 50 Belver Avenue North Kingstown, RI 02852 1.800.453.6866



🖉 Technical Data 卷

Lumirror	FA6
JES	Produ
50.8	- <u>-</u>
14.1	Dat
109	ລ
103	Sh
228	e e e

PROPERTIES		METHOD	UNITS	TYPICAL VALUES	
Thickness		-	micron	38.1	50.8
Nominal Yield		-	m2/kg	18.7	14.1
F-5	MD	- ASTM D882	Мра	109	109
	TD			103	103
Tensile Strength at Break	MD	- ASTM D882	Maa	213	228
	TD		мра –	235	241
Elongation at Break	MD	– ASTM D882	0/	150	160
	TD		70 -	120	130
leat Shrinkage MD	0/	1.2	1.7		
(150°C for 30 minutes)	s) TD ASTM D1204 %	70 -	0.6	0.6	
Coefficient of Friction	A side vs. P side	3-side ASTM D1894	μ_{s}	0.4	0.4
	A-Side VS. D-Side		μ_{D}	0.3	0.4
Gloss (60°)		ASTM D2457	GU	152.0	0.0
Haze (1 sheet)		ASTM 1003	%	6.1	7.5
Surface Roughness Ra (outside surface)		DIN 4768	nm	27.0	29.0
Surface Roughness Ra (inside surface)		DIN 4768	nm	11.0	13.0

Key Features

• One side super smooth and one side rough for excellent handling properties

Winding Direction



* These values do not constitute specific binding specifications

DISCLAIMER: This information is believed to be correct as of the date of issue. Toray Plastics (America), Inc. MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE AND TAKES NO RESPONSIBILITY REGARDING THE SUITABILITY OF THIS INFORMATION FOR THE USER'S INTENDED PURPOSES OR FOR THE CONSEQUENCE OF ITS USE. User is responsible for determining whether the Toray Plastics (America), Inc. product is fit for a particular purpose and suitable for user's method or use of application. Given the variety of factors that can affect the use and application of Toray Plastics (America), Inc. products, which are uniquely within the user's knowledge and control, it is essential that the user make its own tests to determine the safety and suitability of each Toray Plastics (America), Inc. product or product combination for its own purpose.

Lumirror * is a registered trademark of Toray Industries, Inc. for its range of Polyester Films based on Polyethylene Terephthlate (PET).