
## **Applications**

- · Solar control window
- Overlaminate
- Outdoor labels



# SUPER CLEAR UV STABLIZED THREE LAYER PET FILM

### Summary

U6W is a UV-stabilized PET film designed for solar use or over-lamination of inkjet prints and other substrates vulnerable to ultra violet exposure.

Lumirror U6



#### ✓ Technical Data \*\*

PROPERTIES Thickness		METHOD -	<b>UNITS</b> 0.00001"	TYPICAL VALUES	
				92	200
Nominal Yield		-	in²/lb	21,500	9,900
F-5 <b>-</b>	MD	- ASTM D882	lb/in² —	14,800	15,400
	TD			13,800	14,600
Tensile Strength at Break	MD	- ASTM D882	lb/in² —	29,700	26,900
	TD			32,700	31,400
Elongation at Break -	MD	- ASTM D882	% —	170	170
	TD			150	130
Heat Shrinkage (150°C for 30 minutes)	MD	- ASTM D1204	% —	1.2	1.0
	TD			0.4	0.8
Heat Shrinkage (190°C for 5 minutes)	MD	- ASTM D1204	% —	2.1	1.8
	TD			0.7	1.0
Coefficient of Friction	A-side vs. B-side	ASTM D1894	μ <sub>S</sub>	0.4	0.4
	A-side vs. b-side		$\mu_{D}$	0.3	0.3
Haze (1 sheet)		ASTM 1003	%	1.4	1.4


#### Key Features

- Co-extruded three layer structure allows very low haze and friction
- UV protection up to 5-10 years for outdoor applications depending on the conditions

#### Similar Products

- U6W3
- U65V

#### Winding Direction



#### \* These values do not constitute specific binding specifications

DISCLAIMER: This information is believed to be correct as of the date of issue. Toray Plastics (America), Inc. MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE AND TAKES NO RESPONSIBILITY REGARDING THE SUITABILITY OF THIS INFORMATION FOR THE USER'S INTENDED PURPOSES OR FOR THE CONSEQUENCE OF ITS USE. User is responsible for determining whether the Toray Plastics (America), Inc. product is fit for a particular purpose and suitable for user's method or use of application. Given the variety of factors that can affect the use and application of Toray Plastics (America), Inc. products, which are uniquely within the user's knowledge and control, it is essential that the user make its own tests to determine the safety and suitability of each Toray Plastics (America), Inc. product or product combination for its own purpose.

Lumirror \* is a registered trademark of Toray Industries, Inc. for its range of Polyester Films based on Polyethylene Terephthlate (PET).