
Applications

- Confections
- Snacks
- Bakery
- Pet Food
- Graphic
- · Ag/Chem
- Medical
- Electronics



ONE SIDE TREATED, ONE SIDE METALLIZED NON SEALABLE BOPP FILM

Summary

One side vacuum deposited Aluminum on Toray's Ultra High Surface Energy (UHSE), one side corona treated. Designed as a barrier cold seal or buried barrier metallized BOPP film. Ideal for foil and MPET replacement.

Torayfan PC



✓ Technical Data ★

| ✓ Technical Data ★ | | | | | | 77 |
|--|----|------------|------------------------------|----------------|-------|-------------|
| PROPERTIES | | METHOD | UNITS | TYPICAL VALUES | | Product |
| Thickness | | | μm | 12.5 | 15 | |
| Nominal Yield | | | m²/kg | 84 | 73.3 | _ t |
| Tensile Strength at Break - | MD | ASTM D882 | – Мра | 200 | 200 |)ata |
| | TD | | | 300 | 300 | <u> </u> |
| Young's Modulus - | MD | ASTM D882 | – Мра | 1,900 | 1,900 | heet |
| | TD | | | 3,400 | 3,400 | |
| Elongation at Break - | MD | ASTM D882 | - % | 180 | 180 | |
| | TD | | | 60 | 60 | |
| Heat Shrinkage (140°C for 15 minutes) | MD | ASTM D1204 | - % | 8 | 8 | |
| | TD | | | 5 | 5 | |
| COE (Course Treated Cids) | | ASTM D1894 | μ_{s} | 0.36 | 0.36 | |
| COF (Corona Treated Side) | • | | $\mu_{\scriptscriptstyle D}$ | 0.31 | 0.31 | |
| Wetting Tension (Corona Treated Side) | | ASTM D2578 | dyne/cm | 40 | 40 | |
| MVTR - 38 °C, 90% RH | | ASTM F1249 | g/m²/day | 0.08 | 0.08 | |
| O2TR - 23 °C, 0% RH | | ASTM D3985 | cc/m²/day | 9 | 9.3 | |

The product described is covered by one or more of the following patents or patents pending: US6916526

Key Features

- Excellent bonding of pressure sensitive adhesives (cold seals)
- Non craze metal surface
- · Excellent moisture barrier
- · Excellent oxygen barrier

Similar Products

- PC₁
- M10

Typical Structures

- Release Film/ink/ADH/PC3/ Patterned Cold Seal
- PET/ink/PE/PC3/PE
- BOPP/ink/PE/PC3/PE
- Ink/Paper/PE/PC3/PE
- O.L./ink/Board/PE/PC3/PE
- O.L./ink/PC3/PE/Board/PE

Winding Direction



* These values do not constitute specific binding specifications

DISCLAIMER: This information is believed to be correct as of the date of issue. Toray Plastics (America), Inc. MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE AND TAKES NO RESPONSIBILITY REGARDING THE SUITABILITY OF THIS INFORMATION FOR THE USER'S INTENDED PURPOSES OR FOR THE CONSEQUENCE OF ITS USE. User is responsible for determining whether the Toray Plastics (America), Inc. product is fit for a particular purpose and suitable for user's method or use of application. Given the variety of factors that can affect the use and application of Toray Plastics (America), Inc. products, which are uniquely within the user's knowledge and control, it is essential that the user make its own tests to determine the safety and suitability of each Toray Plastics (America), Inc. product or product combination for its own purpose.

Torayfan ® is a registered trademark of Toray Industries, Inc. for its range of bi-oriented Polypropylene Films (BOPP)