
Applications

- · Bar code ribbon
- Fax ribbon
- Word processor ribbon
- · Color ribbon



MONO LAYER PET FILM
WITH ONE SIDE COATED FOR
ADHESION PROMOTION

Summary

F531 is our world standard F53 film, used in thermal transfer ribbon, with a one side coated adhesion promotion layer. The film has excellent thermal stability and good handling properties.

Lumirror F53



Technical Data *

PROPERTIES		METHOD	UNITS 0.00001"	TYPICAL VALUES	
Thickness		-		18	22
Nominal Yield		-	in²/lb	109,800	89,800
F-5	MD	ASTM D882	lb/in² —	16,500	16,200
	TD			15,400	15,100
Tensile Strength at Break	MD	ASTM D882	lb/in² —	43,800	42,700
	TD			36,100	36,300
Elongation at Break	MD	ASTM D882	%	90	100
	TD			110	110
Heat Shrinkage (150°C for 30 minutes)	MD	ASTM D1204	%	2.4	2.2
	TD			1.5	1.5
Coefficient of Friction	A-side vs. B-side	ASTM D1894	μ_{S}	0.3	0.3
			μ_{D}	0.2	0.2


Key Features

- One side is coated for adhesion promotion
- · Good mechanical properties
- · Heat stability
- Good handling properties

Similar Products

- F53
- FA73

Winding Direction



* These values do not constitute specific binding specifications

DISCLAIMER: This information is believed to be correct as of the date of issue. Toray Plastics (America), Inc. MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE AND TAKES NO RESPONSIBILITY REGARDING THE SUITABILITY OF THIS INFORMATION FOR THE USER'S INTENDED PURPOSES OR FOR THE CONSEQUENCE OF ITS USE. User is responsible for determining whether the Toray Plastics (America), Inc. product is fit for a particular purpose and suitable for user's method or use of application. Given the variety of factors that can affect the use and application of Toray Plastics (America), Inc. products, which are uniquely within the user's knowledge and control, it is essential that the user make its own tests to determine the safety and suitability of each Toray Plastics (America), Inc. product or product combination for its own purpose.

Lumirror® is a registered trademark of Toray Industries, Inc. for its range of Polyester Films based on Polyethylene Terephthlate (PET).